
THERMO-OXIDATIVELY STABLE CONDENSATION POLYIMIDES CONTAINING 111-TRIARYL- (U) NATIONAL AERONAUTICS AND SPACE ADMINISTRATION CLEVELAND OH LE B ALSTON ET AL JUL 87 NASA-E-3551 F/G 7/6 AD-A182 290 1/1 UNCLASSIFIED NL





NASA Technical Memorandum 89875 AVSCOM Technical Report 87-C-7

OTIC FILE COPY

Thermo-Oxidatively Stable Condensation Polyimides Containing 1,1,1-Triaryl-2,2,2-Trifluoroethane Dianhydride and Diamine Monomers

William B. Alston
Propulsion Directorate
U.S. Army Aviation Research and Technology Activity—AVSCOM
Lewis Research Center
Cleveland, Ohio

and

Roy F. Gratz Mary Washington College Fredericksburg, Virginia



Prepared for the Symposium on Recent Advances in Polyimides and Other High Performance Polymers sponsored by the American Chemical Society Reno, Nevada, July 13-16, 1987

Approved for public released
Distribution Unlimited





THERMO-OXIDATIVELY STABLE CONDENSATION POLYIMIDES CONTAINING

1.1.1-TRIARYL-2.2.2-TRIFLUOROETHANE DIANHYDRIDE

AND DIAMINE MONOMERS

William B. Alston
Propulsion Directorate
U.S. Army Aviation Research and Technology Activity - AVSCOM
Lewis Research Center
Cleveland, Ohio 44135

and

Roy F. Gratz
Department of Chemistry, Geology, and Physics
Mary Washington College
Fredericksburg, Virginia 22401


SUMMARY

The presence of the hexafluoroisopropylidene (6F) connecting group in aryl dianhydrides used to prepare aromatic polyimides provides high glass transition temperature (Tg) polyimides that exhibit excellent thermo-oxidative stability. The purpose of this study was to determine if a trifluorophenylethylidene (1-phenyl-2,2,2-trifluoroethane, 3F) connecting group would have a similar effect as a 6F group on the thermo-oxidative stability of aromatic polyimides. A new dianhydride containing the 3F connecting group was synthesized. This new 3F dianhydride and a previously reported (refs. 1 to 3) aromatic diamine also containing the 3F connecting group were used together and in various combinations with known diamines or known dianhydrides, respectively, to prepare new condensation polyimides which contained the 3F group in one or both of the monomers comprising the polymer repeat unit. Known polyimides, including some with the 6F connecting linkage, were also prepared for comparison purposes. The new 3F containing polymers and the analogous comparison 6F polymers were prepared by condensation polymerization via the traditional amic-acid polymerization method in N.N-dimethylacetamide (DMAc) solvent. The amic-acid solutions, with two exceptions, had inherent viscosities greater than 0.45 dl/g, indicating that high molecular weight polymers had been formed. Structure-toproperty relationships correlating inherent viscosity to the basicity of those diamine monomers which contained 3F and 6F connecting linkages were observed and explained in a prior report (ref. 3). The solutions were cast as amic-acid films and then thermally converted into polyimide films at 300 to 500 °C, usually 350 °C. in a nitrogen atmosphere. The polyimide films were then pulverized into molding powders which, in turn, were processed into neat resin discs at temperatures and pressures as high as 468 °C/34.5 MPa. Additional resin discs were processed with similar conditions from molding powders of some 3F monomer combinations that were prepared using other techniques as described in reference 3. These techniques included precipitation of the amic-acid molding powders from DMAc amic-acid solutions, thermal or chemical imidization of the dried precipitated amic-acid powders, and preparation from stoichiometric amounts of diamine and diacid-diester monomer mixtures. The Tg's of these films and resin discs were then determined by thermomechanical analysis (TMA)


and were the subject of a prior report (ref. 3) which identified two new polyimides of Tg \geq 371 °C (3F dianhydride/paraphenylene diamine (PPDA), Tg \sim 370 °C, and pyromellitic dianhydride (PMDA)/3F diamine, Tg ~440 °C). The thermal and thermo-oxidative stability of these 3F polyimide films and the comparison 6F polyimide films were then determined by thermogravimetric analysis (TGA). The isothermal weight losses of the films and the resin discs at 316 °C, 371 °C, and also at 371 °C under 0.5 MPa (~5 atm) air pressure were then determined (using a weight loss/unit surface area basis). The results of these studies identified two new 3F containing polyimides (3F dianhydride/PPDA and 6F dianhydride/3F diamine) with low rates of weight loss/unit surface area compared to the known very oxidatively stable 6F dianhydride/PPDA and PMDA/6F diamine resins. The study also showed that the resin discs exhibited the same overall trends in weight loss/unit surface area as their respective films, however, the weight loss per unit surface area of the discs was about an order of magnitude greater. This was presumably due to some mechanical degradation induced during the grinding of the molding powders and/or a greater internal (thus, unmeasured) surface area in the resin discs compared to the films. These overall results indicate that polyimides containing the 3F linkage exhibit thermal and thermo-oxidative stability comparable to polyimides containing the 6F linkage. These thermo-oxidative stability results, combined with the prior Tg results (ref. 3), show that further development of the 3F connecting linkage in aryl dianhydride and aryl diamine monomers to produce high Tg, thermo-oxidatively stable polyimides suitable for 371 °C resin and composite applications continues to be warranted.

REFERENCES

- 1. Kray, W.D. and Rosser, R.W., <u>J. Org. Chem.</u>, 1977, <u>42</u>, 1186-1189.
- 2. Alston, W.B., in "High Temperature Polymer Matrix Composites" NASA CP-2385, 1985, pp. 187-205. (Also, U.S. Army AVSCOM-TR-85-C-7).
- 3. Alston, W.B. and Gratz, R.F., in "Recent Advances in Polyimide Science and Technology," Society of Plastics Engineers: Poughkeepsie, NY, 1987, pp. 1-15. (Also NASA TM-87113, and U.S. Army AVSCOM-TR-85-C-18).



GF DIAMHYDRIDE, GFDA



GF DIAMINE, GFDAM

3F DIANHYDRIDE, 3FDA

SF DIAMINE, SFDAM



Accesion For		
NTIS CRA&I	A)	7
DTIC TAB		١
Una indicated in Just haution	()	
By		-
All ribbinity	Se toe	
Det Avil a		Ì
1 .		

1. Report No. NASA TM-89875 AVSCOM-TR-87-C-	2. Government Accession No.	3. Recipient's Catalog No.
4. Title and Subtitle		5. Report Date
Thermo-Oxidatively Stab Containing 1,1,1-Triary Dianhydride and Diamine		6. Performing Organization Code 505-63-01
7. Author(s)		8. Performing Organization Report No.
William B. Alston and Roy F. Gratz		E-3551
		TO. WORK OTHER NO.
9. Performing Organization Name and Address NASA Lewis Research Center and Propulsion Directorate,		11. Contract or Grant No.
	arch and Technology Activity	
AVSCOM, Cleveland, Ohio 44135		13. Type of Report and Period Covered
2. Sponsoring Agency Name and Address		Technical Memorandum
National Aeronautics and Space Administration Washington, D.C. 20546 and U.S. Army Aviation Systems Command, St. Louis, Mo. 63120		14. Sponsoring Agency Code
	analysis (TGA), and isother	rmal watcht lock data (at
films. The films were thermally processed und characterized by $T_g^{\sigma \sigma}$ study identified two ne polyimides with low rat overall trends in T_g weight loss per unit su to mechanical degradati overall results indicat linkage have $T_{\sigma \sigma}$ and	pulverized into molding power pressure into neat resin and 316 and 371 °C isothermown polyimides with Tas greates of weight loss. The resident design and weight loss as the responsible area was always greated on induced during preparation that polyimides containing thermo-oxidative stability of	ure) were obtained for the ders which, in turn, were discs. The discs were also all weight losses. The film ater than 371 °C and two new in discs exhibited the same
films. The films were thermally processed und characterized by T_g^{rs} study identified two ne polyimides with low rat overall trends in T_g weight loss per unit su to mechanical degradati overall results indicat	pulverized into molding power pressure into neat resin and 316 and 371 °C isotherms with Tas greates of weight loss. The resident and weight loss as the respective area was always greated on induced during preparation thermo-oxidative stability corropylidene group.	ure) were obtained for the ders which, in turn, were discs. The discs were also al weight losses. The film ater than 371 °C and two new in discs exhibited the same active films, however the er, presumably due to voids or on of the molding powders. The g the trifluorophenylethylidene comparable to polyimides con-
films. The films were thermally processed und characterized by Tgs study identified two ne polyimides with low rat overall trends in Tg weight loss per unit su to mechanical degradati overall results indicat linkage have Tgs and taining the hexafluoroi	pulverized into molding power pressure into neat resin and 316 and 371 °C isothermometry in the polyimides with Tas greates of weight loss. The resident and weight loss as the respectance area was always greated in induced during preparation induced during preparation thermo-oxidative stability containing thermo-oxidative stability containing the polyimides.	ure) were obtained for the ders which, in turn, were discs. The discs were also al weight losses. The film ater than 371 °C and two new in discs exhibited the same ective films, however the er, presumably due to voids or on of the molding powders. The g the trifluorophenylethylidene comparable to polyimides con-
thermally processed und characterized by Tgs study identified two ne polyimides with low rat overall trends in Tg weight loss per unit su to mechanical degradati overall results indicat linkage have Tgs and taining the hexafluoroi	pulverized into molding power pressure into neat resin and 316 and 371 °C isotherms with Tas greates of weight loss. The resident and weight loss as the respectance area was always greated on induced during preparation that polyimides containing thermo-oxidative stability copropylidene group.	ure) were obtained for the ders which, in turn, were discs. The discs were also al weight losses. The film ater than 371 °C and two new in discs exhibited the same active films, however the er, presumably due to voids or on of the molding powders. The g the trifluorophenylethylidene comparable to polyimides con-
thermally processed und characterized by Tgs study identified two ne polyimides with low rat overall trends in Tg weight loss per unit su to mechanical degradati overall results indicat linkage have Tgs and taining the hexafluoroi temperature (Tg); Therm oxidatively, stable	pulverized into molding power pressure into neat resin and 316 and 371 °C isotherms with Tas greates of weight loss. The residence area was always greated on induced during preparation thermo-oxidative stability containing the stability co	ure) were obtained for the ders which, in turn, were discs. The discs were also al weight losses. The film ater than 371 °C and two new in discs exhibited the same ective films, however the er, presumably due to voids or on of the molding powders. The g the trifluorophenylethylidene comparable to polyimides con-
films. The films were thermally processed und characterized by Tgs study identified two ne polyimides with low rat overall trends in Tg weight loss per unit su to mechanical degradati overall results indicat linkage have Tgs and taining the hexafluoroi They was (Suggested by Author(s)) Polyimides; Condensatio temperature, stability; temperature (32); Therm	pulverized into molding power pressure into neat resin and 316 and 371°C isotherms with Tas greates of weight loss. The resident and weight loss as the respectance area was always greated on induced during preparation induced during preparation thermo-oxidative stability containing the sta	ure) were obtained for the ders which, in turn, were discs. The discs were also all weight losses. The film ater than 371 °C and two new in discs exhibited the same ective films, however the er, presumably due to voids or on of the molding powders. The g the trifluorophenylethylidene comparable to polyimides con-

EMD

7 - 8 7

1